



3M Science.
Applied to Life.™

3M™ Scotch® Industrial Box Sealing Tape 371

Last Revision Date: May, 2017

Product Description

Scotch® Box Sealing Tape 371 is an industrial packaging tape used for box sealing, splicing, recoupage and other packaging applications. This product has a conformable backing and a consistent pressure sensitive hot melt synthetic rubber adhesive system.

Product Features

- Adheres instantly to a variety of surfaces.
- Edge tear and split resistance.
- Good adhesion to fiberboard.
- Roll to roll consistency increases productivity for improved unit costs.
- Meets FDA requirements for indirect food contact.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values	Additional Information
Backing	Biaxially oriented polypropylene	
Adhesive Type	Pressure sensitive hot melt rubber-resin	
Color	Blue, clear, green, orange, red, tan, yellow, and white	
Backing Thickness (mm)	0.03 mm	View
Test Method: ASTM D3652		
Total Tape Thickness (mil)	1.8 mil	View
Test Method: ASTM D3652		
Total Tape Thickness (mm)	0.046 mm	View
Test Method: ASTM D3652		

Backing Thickness	1.2 mil	View 
Test Method: ASTM D3652		
Holding Power	3,500+ min	View 
Test Method: ASTM D3654		
Substrate: Fiberboard		

Typical Performance Characteristics

Property	Values	Additional Information
180° Peel Adhesion	40 oz/in	View 
Test Method: ASTM D3330		
Notes: 12 in/min (300 mm/min)		
180° Peel Adhesion	43.8 N/100mm	View 
Test Method: ASTM D3330		
Substrate: Stainless Steel		
Tensile Strength	385 N/100mm	View 
Test Method: ASTM D3759		
Tensile Strength	22 lb/in	View 
Test Method: ASTM D3759		
Tensile Strength	771 N/100mm	View 
Test Method: ASTM D3759		
Tensile Strength	44 lb/in	View 
Test Method: ASTM D3759		
Elongation at Break (%)	160 %	View 
Test Method: ASTM D3759		

Available Sizes

Property	Values	Additional Information
Standard Roll Length	50, 100, 914, 1500 m	

Standard Roll Length	55, 109, 1000, 1641 yd
Standard Width	36, 42, 48, 72 mm
Standard Width	1.4, 1.7, 1.9, 2.8 in
Core Size (ID)	76.2 mm
Core Size (ID)	3 in

Storage and Shelf Life

Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40 to 50% relative humidity are recommended. To obtain best performance, use this product within 18 months from date of manufacture.

Industry Specifications

Meets FDA requirements for indirect food contact.

Bottom Matter

3M
 Industrial Adhesives and Tapes Division
 3M Center, Building 225-3S-06
 St. Paul, MN 55144-1000
 800-362-3550

Trademarks

Scotch is a registered trademark of 3M.

Handling/Application Information

Application Techniques

An extensive line of application equipment including hand held manual dispensers and semi-automatic and fully automatic equipment is available. Application of Scotch® Box Sealing Tape 371 is most easily accomplished at room temperature. At colder temperatures, approaching 32°F (0°C), the adhesive becomes more firm. Once applied, Scotch® Tape 371 performs well throughout the normal temperature ranges typically encountered by packaged products in shipping and storage environments.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/p/d/b40067745/
Safety Data Sheet SDS	https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=371

Family Group

Link Tags:



Products	Backing	Adhesive Type	Color	Backing Thickness (mm)	Total Tape Thickness (mm)
371	Biaxially oriented polypropylene	Pressure sensitive hot melt rubber-resin	Blue, clear, green, orange, red, tan, yellow, and white	0.03 mm	0.046 mm
371+	Biaxially oriented polypropylene	Pressure sensitive hot melt rubber-resin	Clear	0.03 mm	0.048 mm

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.